

## Built in terminal -Text-

### 2 row text terminal – value for money

This low cost terminal has a 2 row backlighted text display; 6 up to 24 membrane keys and 6 LEDs. This unit is suitable for small budget applications to display and control the process.



### Technical features

Technical data	Power supply:	9...30 Vdc
	Operating temperatur:	0...55 °C (optional: -20...65 °C)
Display	LCD-display:	Text display 16 x 2 signs (optional: backlighted)
	LEDs:	0 (optional: up to 6)
Operation panel	Membrane keys:	6 optional: customised layout, up to 24 keys
	Interfaces	Alternatives
Electronic	CAN:	10 kBit/s...1 MBit/s
	RS485:	1200...38400 Bit/s
	RS232:	1200...38400 Bit/s
	Processor:	SAB C515C
System software	EPROM:	64 kByte
	EEPROM:	512 Byte
	RAM:	32 kByte
	Alternatives:	VT 100 - terminal-emulation C-driver for own application developments Implementations on customer demands possible
Enclosure	Sizes:	144 (w) x 72 (h) x 70 (d) mm
	Protection class:	IP52 (optional: IP65)
	Material:	PS
	Colour:	black(others on request)
	Connections:	Screw/Plug-connector

**Order no.: 70050**

Technical changes without prior notice possible.

Released: 8/2008